SEARCHED INDEXED



FIG. 1


57
56
52
OPTIONAL KEYBOARD
OPTIONAL FLASH
ORIENTATION SENSOR
OPTIONAL USB PORT
58
PROGRAM ROM MEMORY
70
AREA IMAGE SENSOR
64 MBIT DRAM
33
2
ARTCAM CENTRAL PROCESSOR (ACP)
OPTIONAL STEREO 3D AREA IMAGE SENSOR
54
PRINT ROLL
42
4
53
OPTIONAL COLOR DISPLAY
PRINT HEAD
41
8
GUILLOTINE PHOTO
5
40
49
31
ARTCARD SENSOR
66
STATUS LED
30
65 ARTCARD
BUTTONS
60
PAPER TRANSPORT MOTOR
36
9
61
ARTCARD MOTOR
37
STATUS LCD
15
34
62
ZOOM MOTOR
38
POWER MANAGEMENT CIRCUIT
BATTERY
SYSTEM POWER
63
AUTOFOCUS MOTOR
48
51
39

FIG. 2


70
4 MByte Flash EEPROM
RAMbus DRAM Interface
81
Clock PLL
JTAG Interface
85
77
Program Cache
83
Area Sensor Interface
72
CPU Core
Data Cache
76
Image LCD Interface
DAC
88
182
CPU Memory Decoder
68
84
78
Input FIFO
Microcode
Address Gen
FIFO
ALU
178
Numeric LCD Interface
87
Crossbar Switch
Antcard Scanner Interface
84
Output FIFO
Print Head Interface
79
67
74
Parallel Interface
Authentication Chip Interface
64
Universal Sertial Bus (USB) Port
52
Infra-red Keyboard Interface
55

31

FIG. 3


74
182
196
190
189
184
Microcode
Address Gen.
FIFO
FIFO
Address Gen.
178
ALU
Crossbar
Switch
-183-
188
185
195

FIG. 3(a)


187
I/O ADDRESS GENERATOR 1
INPUT FIFO
FIFO FULL
FIFO EMPTY
CACHE BUS 1
STATE MACHINE
REGIS TERS
FIFO EMPTY
FIFO FULL
190
OUTPUT FIFO
186
I/O ADDRESS
INPUT FIFO
FIFO FULL
FIFO EMPTY
CACHE BUS2
STATE MACHINE
REGIS TERS
FIFO EMPTY
FIFO FULL
189
OUTPUT FIFO
FIEQ EMPTY
VLIW INPUT FIFO
78
VLIW OUTPUT FIFO
FIFO FULL
79
188
ALU
OUT1
OUT2
IN1
IN2
EXTERNAL CROSSBAR (8 IN, 8 OUT)
STATUS BIT
SELECT INPUTS FROM CROSSBAR
194
STATUS BITS
CSTATUS
200
SYNC BITS
CSYNC
196
STATE MACHINE
SUSPEND PROCESS
198
MICROCODE RAM
196
CSTATUS = COMMON STATUS REGISTER
CSYNC = COMMON SYNCHRONIZATION REGISTER
178

FIG. 4


188
203
EXTERNAL CROSSBAR
WRITE
TO OUTPUT FIFO'S
IN
207
STATUS BIT
1 BIT
16 BITS
32 BITS
OUT
208
CROSSBAR1
8 IN
7 OUT
213
REGISTERS
215
ADDER BLOCK
204
MULTI-PLY BLOCK
206
210
206
L
BS
CROSSBAR2
4 IN
6 OUT
FROM INPUT FIFO'S
S
211
READ
R
M
209
202
212
214

FIG. 5


32 BITS
CONTROL
IN1
1
DATA FROM
EXTERNAL CROSSBAR
IN2
1
TO CROSSBAR1

FIG. 6


FROM CROSSBAR1 (IN1,IN2,OUT1,OUT2,D0-D3)
FROM CROSSBAR2 (M,L,S,R)
2
2
0
1
K1
K2
1
OUT1
1
OUT2
32 BITS
CONTROL
TO EXTERNAL CROSSBAR,
CROSSBAR1 AND WRITE

FIG. 7


FROM CROSSBAR$_1$ (IN_1,IN_2,OUT_1,OUT_2,D_0-D_3)
FROM CROSSBAR$_2$
(M,L,S,R)
2
2
0
1
K_1
K_2
1
D_0
1
D_1
1
D_2
1
D_3
TO CROSSBAR$_1$
32 BITS
CONTROL

FIG. 8


IN_1 IN_2 OUT_1 OUT_2
D_0
D_1
D_2
D_3
CROSSBAR$_1$
TO MULTIPLY/
INTERPOLATE
TO ADDER
32 BITS
TO
REGISTERS
TO OUT

FIG. 9


M
L
S
R
CROSSBAR2
TO MULTIPLY/
INTERPOLATE
TO ADDER
TO OUT
TO REGISTERS
32 BITS

FIG. 10


2
2
4
FROM
INPUT
FIFO'S
PAD/
EXTEND
BARREL
SHIFT
R
1 BIT
16 BITS
32 BITS
CONTROL
2
STATUS BIT

FIG. 11



FIG. 12



FIG. 13



FIG. 14


K1
K2
K3
K4
FROM CROSSBAR1
RESULT FROM ADDER
0
1
FROM CROSSBAR1
2
2
2
2
FROM CROSSBAR2
2
2
2
P1
P2
5
FGEN
5
AGEN
5
BGEN
INTERP
INTERP
INTERP
INTERP
3
+
+
+
+
2
1
M
1
TST
1
STATUS BIT
1 BIT
8 BITS
16 BITS
32 BITS
CONTROL

FIG. 15



FIG. 16

ORDER OF PIXELS PRESENTED BY A SEQUENTIAL READ ITERATOR ON A 4 X 2 IMAGE WITH PADDING.



FIG. 17


SEQUENTIAL READ ITERATOR
PROCESS PIXEL
SEQUENTIAL WRITE ITERATOR
141
140
142

FIG. 18

A 3×3 BOX VIEW TRAVERSES THE PIXELS IN ORDER: 0,1,2,3,4,5,6,7,8 ETC, PLACING A 3×3 BOX CENTERED OVER EACH PIXEL...

3×3 BOX VIEW OF FIRST PIXEL IN IMAGE = 9 PIXELS, 5 OF WHICH ARE OUTSIDE THE IMAGE



152

FIRST 9 PIXELS FROM THE BOX READ ITERATOR:

IF DUPLICATION OF EDGE PIXELS IS ON:
0,0,0,0,0,1,4,4,5

IF DUPLICATION OF EDGE PIXELS IS OFF:
V,V,V,V,0,1,V,4,5
WHERE V IS CONSTANT
"OUTSIDE IMAGE" PIXEL VALUE

153

3×3 BOX VIEW OF SECOND PIXEL IN IMAGE = 9 PIXELS, 3 OF WHICH ARE OUTSIDE THE IMAGE



SECOND 9 PIXELS FROM THE BOX READ ITERATOR:

IF DUPLICATION OF EDGE PIXELS IS ON:
0,1,2,0,1,2,4,5,6

IF DUPLICATION OF EDGE PIXELS IS OFF:
V,V,V,0,1,2,4,5,6
WHERE V IS CONSTANT
"OUTSIDE IMAGE" PIXEL VALUE

FIG. 19


BOX READ ITERATOR
FILTER OR CONVOLVE
SEQUENTIAL WRITE ITERATOR
160
162
161

FIG. 20


IMAGE BROKEN INTO VERTICAL STRIPS, EACH STRIP IS 32 PIXELS ACROSS.
STRIP 0
STRIP 1
STRIP 2
169
170
LINES ARE ACCESSED LINE 0 TO LINE N WITHIN A SINGLE STRIP.
166
LINE 0
LINE 1
LINE 2
LINE 3
LINE 4
LINE N
167
PIXELS ARE ACCESSED PIXEL 0 - PIXEL 31 WITHIN A SINGLE LINE.
P0 P1 P2 ... P31
165

FIG. 21


'RANDOM ACCESS' READER
CALCULATE OUTPUT PIXELS
VERTICAL-STRIP WRITE ITERATOR

FIG. 22



FIG. 23



FIG. 24


GENERATE
VERTICAL
STRIP [X,Y]
X
Y

FIG. 25


0
REG1
REG2
+
1
X
+
K1
K1
-
REG3
MIN
K2
CONTROL
Y
0
REG4
+
1
-
K3
CONTROL

FIG. 26



2×2 PIXEL BLOCK FROM CCD

FIG. 27



FIG. 28

SEARCH REQUEST



FIG. 29



2×2 PIXEL BLOCK FROM CCD

FIG. 30



FIG. 31



FIG. 32



FIG. 33


240
TIME
READ PIXEL DATA FROM CCD
PHASE 1
PHASE 2
PHASE 3
PHASE 4

FIG. 34


34
ARTCARD
CCD
9
230
DOT SAMPLED
OVER 3x3 PIXELS
231
DOT SAMPLED
OVER 4x4 PIXELS

FIG. 35


1 COLUMN
10
ARTCARD
9
THE DRIFT OF DOTS ACROSS THE COLUMNS OF PIXELS, EXAGGERATED.
THE ACTUAL DRIFT IS 166 COLUMNS OVER 9450 PIXELS (A 1 COLUMN SHIFT EVERY 57 PIXELS).
CCD
166 PIXELS
1 DEGREE
9450 PIXELS

FIG. 36


220
READ LINEAR CCD
ARTCARD PIXEL DATA
221
DECODE BITMAP
ENCODED, XORed, SCRAMBLED BITMAPPED DATA
222
BITMAP TO BYTES
ENCODED, XORed, SCRAMBLED DATA
223
CHECKERBOARD XOR
ENCODED, SCRAMBLED DATA
224
227
UNSCRAMBLE
ENCODED, UN-SCRAMBLED DATA
225
REED-SOLOMON DECODE
RAW DATA
226

FIG. 37


TARGET 0 (241)
9
THE TOP OF THE VERTICAL CLOCK MARK COLUMN AT THE LEFT OF THE DATA AREA IS EXACTLY 24 DOTS TO THE RIGHT OF THE CENTER OF THE TOPMOST TARGET.
24 DOTS
244
31 DOTS (93 PIXELS)
239
192 DOTS (576 PIXELS)
31 DOTS (93 PIXELS)
DATA AREA
270
276
TARGET 1
277

FIG. 38


31 DOTS
242
31 DOTS
241
LOGICAL BAND BOUNDARIES

FIG. 39


245
246
RUN LENGTH ENCODER
FILTER
PIXELS
254
S2 START PIXEL
247
FIFO
S1
S2
S3
...
248
253
252
1BIT
7BITS
BIT VALUE
RUN LENGTH
249
250

FIG. 40



FIG. 41


294
292
290
CASE 1
295
291
293
292
CASE 2
291
294
293
292
291
CASE 3
295
294
293
291
CASE 4
294
293

FIG. 42


301
300
PIXEL 1 (4 BITS)
PIXEL 2 (4 BITS)
PIXEL 3 (4 BITS)
LOOKUP TABLE
DOT VALUE (1 BIT)
302

FIG. 43


312
313
314
315
PREV-1 COLUMN (DOT)
PREV COLUMN (DOT)
CURRENT COLUMN (DOT)
311
PREV ROW (DOT)
317
CURRENT ROW (DOT)
310
NEXT ROW (DOT)

FIG. 44


321
BIT HISTORY (3 BITS)
(CENTROID FRACTIONAL COMPONENT - 0.5)/16
320
323
324
EXPECTED PIXELS (20 BITS)
ACTUAL PIXELS (20 BITS)
-, +
PIXELS DIFFERENCE
(6 BITS)
326
321
327

FIG. 45


334
331
332
2MB SCRAMBLED
2MB UNSCRAMBLED
335
SYMBOL BLOCK 0 (HAVING SYMBOL 0 FROM ALL THE CODE WORDS)
ETC.
SYMBOL BLOCK 15 (HAVING SYMBOL 15 FROM ALL THE CODE WORDS)
ETC.
330
UNSCRAMBLE & XOR
CODE WORD 0
CODE WORD n

FIG. 46


BLACK AND WHITE DOTS
BLACK DOT SURROUNDED BY WHITE
WHITE DOT SURROUNDED BY BLACK

FIG. 47


1101
1106
1104
8 DATA BLOCKS (8 BLOCKS + 7 GAPS = 5072 DOTS)
1102
1103
WHITE BORDER REGION
8 DATA BLOCKS (8 BLOCKS + 7 GAPS = 3208 DOTS)
8 WHITE DOT GAP BETWEEN DATA BLOCKS IN HORIZONTAL & VERTICAL DIMENSIONS
ACTIVE REGION CONTAINING 64 DATA BLOCKS

FIG. 48


1107
TOTAL WIDTH
627 DOTS
1108
TOTAL HEIGHT
394 DOTS
DATA REGION
595 X 384 DOTS
(228,430 DOTS)
1111
DATA BLOCK
1109


DATA REGION
(384 DOTS
HIGH)
UPPER BORDER &
CLOCKMARKS
(5 DOTS HIGH)
LOWER BORDER &
CLOCKMARKS
(5 DOTS HIGH)
VERTICAL STRUCTURE OF DATA
BLOCK


DATA REGION
(595 DOTS WIDE)
LEFT TARGETS
(15 DOTS WIDE)
RIGHT TARGETS
(15 DOTS WIDE)
WHITE DOT
ORIENTATION COLUMN
(1 DOT WIDE)
BLACK DOT
ORIENTATION COLUMN
(1 DOT WIDE)
HORIZONTAL STRUCTURE OF DATA
BLOCK

FIG. 49



FIG. 51

FIG. 52

FIG. 50


1122
15 DOTS WIDE
CENTER OF TARGET IS WHITE CROSS
(1121)
2 BLACK DOTS BEFORE TARGET ID
TARGET NUMBER ID IS 2 DOTS WIDE.
SINCE THIS ID IS 4 DOTS LONG
15 DOTS HIGH
1120
2 BLACK COLUMNS BEFORE TARGET ID
2 BLACK COLUMNS AFTER TARGET ID

FIG. 53


6 LEFT TARGETS
6 RIGHT TARGETS
1118
1116
1117
DATA REGION

FIG. 54


1123
1126
55 DOTS
1124
TARGET
15 DOTS
55 DOTS
15 DOTS
1125
TARGET 2

FIG. 55


1127
LEFT TARGET #1
1128
RIGHT TARGET #6
LEFT ORIENTATION COLUMN IS WHITE
RIGHT ORIENTATION COLUMN IS BLACK

FIG. 56



FIG. 57

00:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	32 COPIES OF THE 3 BYTE CONTROL INFORMATION
0C:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
18:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
24:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
30:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
3C:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
48:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
54:	4F	00	3D	4F	00	3D	4F	00	3D	4F	00	3D	
60:	00	00	00	00	00	00	00	00	00	00	00	00	RESERVED BYTES ARE 0
6C:	00	00	00	00	00	00	00	00	00	00	00	00	
78:	00	00	00	00	00	00	00	00	00	00	00		

FIG. 59



FIG. 58



FIG. 60



FIG. 61



FIG. 62

SEARCH REPORT



FIG. 63


3 CCD SENSORS SCANNING DOTCARD
OVERLAP CAUSES BLURRING
SENSED AREA
DOTCARD SURFACE

FIG. 64


RANGE OF BLACK DOTS (FREQUENCY
RANGE OF WHITE DOTS (FREQUENCY
30
20
10
50
100
150
200
250
CENTER DOT PIXEL VALUE

FIG. 65



FIG. 66



APPROXIMATE DATA SIZES FOR 1600 DPI DOTCARD

86MM + 1MM IN HORIZONTAL DIMENSION FOR 1° ROTATION = 87MM
87MM = 16,252 SCANLINES
16,440 SCANLINES @ 11,000 PIXELS PER SCANLINE = 180,840,000 PIXELS
180,840,000 PIXELS @ 1 BYTE PER PIXEL = 180,840,000 BYTES = 172.5 MB

64 DATA BLOCKS, EACH CONTAINING 597 COLUMNS (595 DATA REGION COLUMNS AND 2 ORIENTATION COLUMNS), @ 48 BYTES PER COLUMN = 28,656 BYTES PER DATA BLOCK FOR A TOTAL OF 1,833,984 BYTES.

64 DATA BLOCKS, EACH CONTAINING 112 ENCODED REED SOLOMON BLOCKS, @ 255 BYTES PER REED SOLOMON BLOCK FOR A TOTAL OF 1,827,840 BYTES.

DECODED DATA, WITH A MAXIMUM SIZE OF 910,082 BYTES. (64 X 112 X 127 – (2 CONTROL BLOCKS @ 127 BYTES))

FIG. 67


PARALLEL PROCESSES
PROCESS 2 – DETECT START OF DOTCARD
PROCESS 3 – EXTRACT BIT DATA FROM PIXELS
PROCESS 1 – READ PIXEL DATA FROM CCD
TIME

FIG. 68


PROCESS 1 READ PIXEL DATA FROM CCD
190 COLUMN WINDOW OF PIXELS
PROCESS 2 DETECT START OF DOTCARD
CCD
PROCESS 3 EXTRACT BIT DATA FROM PIXELS
SCRATCH DATA
DOTCARD BIT IMAGE
PIXEL DATA
BIT-IMAGE DATA
SCRATCH DATA

FIG. 69



FIG. 70



FIG. 71



FIG. 72


8 SEGMENTS,
EACH CONTAINING
8 DATA BLOCKS

FIG. 73


GATHER
MIN & MAX
MIN
MAX
FILTER
RUN-LENGTH
ENCODER
PIXELS
S0
S1
S2
S3
TARGE
TS
FIND
TARGETS
COLOR
VALUE
RUN LENGTH

FIG. 74



FIG. 75



$$\text{Lanczos}\,3(x) = \begin{cases} \dfrac{\sin(\pi x)}{\pi x}\,\dfrac{\sin\left(\pi\dfrac{x}{3}\right)}{\pi\dfrac{x}{3}}, & |x| < 3 \\ 0, & |x| \geq 3 \end{cases}$$

FIG. 76



FIG. 77


PARALLEL PROCESSES
PROCESS 1 –REORGANIZE THE BIT IMAGE
PROCESS 2 – UNSCRAMBLE THE ENCODED DATA
PROCESS 3 – REED-SOLOMON DECODE DATA
TIME

FIG. 78


PROCESS 1 REORGANIZE BIT IMAGE
SCRAMBLED ENCODED DATA
PROCESS 2 UNSCRAMBLE THE ENCODED DATA
DOTCARD BIT IMAGE
PROCESS 3 REED-SOLOMON DECODE DATA
UNSCRAMBLED ENCODED DATA
DECODED DATA
BIT-IMAGE DATA
DECODED DATA

FIG. 79


SCRAMBLED DATA
UNSCRAMBLED DATA
ALL THE BYTE OS FROM THE 7168 CODE WORDS
255 BLOCKS EACH 7168 BYTES LONG (1,827,840 BYTES)
ALL THE BYTE 2555 FROM THE 7168 CODE WORDS
UNSCRAMBLE
CODE WORD 0
7168 REED-SOLOMON ENCODED BLOCKS OF DATA (1,827,840 BYTES)
CODE WORD 7167

FIG. 80


KERNEL SEQUENTIAL READ ITERATOR
0
BOX READ ITERATOR
*
+
LATCH1
SEQUENTIAL WRITE ITERATOR
1
LATCH2
-
K1
CONTROL SIGNAL

FIG. 81


340
CONVOLVE COEFFICIENT KERNEL
346
342
341
344
BOX READ ITERATOR
FILTER OR CONVOLVE
SEQUENTIAL WRITE ITERATOR

FIG. 82


FOREGROUND SEQUENTIAL READ ITERATOR
352
BACKGROUND SEQUENTIAL READ ITERATOR
353
351
α CHANNEL SEQUENTIAL READ ITERATOR
COMPOSITE
350
355
SEQUENTIAL WRITE ITERATOR

FIG. 83


FOREGROUND SEQUENTIAL READ ITERATOR
BACKGROUND SEQUENTIAL READ ITERATOR
K1
-
*
*
+
SEQUENTIAL WRITE ITERATOR
α CHANNEL SEQUENTIAL READ ITERATOR
>>16

FIG. 84


A
365
B
WARP MAP
0→MAX. VALUE
C
366
D
OUTPUT
IMAGE
E
F
INPUT
IMAGE
367

FIG. 85


P2 HISTORY
366
P0 HISTORY
365
CALCULATE
SPAN
SPAN
P1
364

FIG. 86

SAMSUNG EXHIBIT 1060



FIG. 87


P2=PREVIOUS LINE'S POINT
P0=PREVIOUS POINT ON SAME LINE
P1=CURRENT POINT

FIG. 88

SUBSTITUTE SHEET



FIG. 89


POINT (x,y) ON LEVEL B OF PYRAMID
LEVEL B OF PYRAMID ($ln_2 s+1$)
370
LEVEL A OF PYRAMID ($ln_2 s$)
371
POINT (x,y) ON LEVEL A OF PYRAMID

FIG. 90


INTERPOLATE IN Y (LEVEL B)
INTERPOLATE IN X (LEVEL B)
INTERPOLATE IN X (LEVEL B)
373
INTERPOLATE ACROSS SPAN
INTERPOLATE IN X (LEVEL A)
INTERPOLATE IN X (LEVEL A)
INTERPOLATE IN Y (LEVEL A)

FIG. 91


378
377
SEQUENTIAL READ ITERATOR
PRODUCE HISTOGRAM
HISTOGRAM

FIG. 92


NEW COLOR TABLE
380
382
381
383
SEQUENTIAL READ ITERATOR
LOOKUP COLOR
SEQUENTIAL WRITE ITERATOR

FIG. 93



FIG. 94



FIG. 101


CHANNEL X V-STRIP READ ITERATOR
CHANNEL Y V-STRIP READ ITERATOR
CHANNEL Z V-STRIP READ ITERATOR
LATCH1
LATCH2
LATCH3
LU1
TRI-LINEAR INTERPOLATE
CHANNEL N V-STRIP WRITE ITERATOR

FIG. 95


K4
K5
K6
K1
K2
K3
YOUT
XOUT
LATCH1
LATCH2
LATCH3
LATCH4
YIN
XIN

FIG. 96


Y_{IN}
X_{IN}
LU_1
BILINEAR INTERPOLATE
PIXEL

FIG. 97


SEQUENTIAL READ ITERATOR
SCALE IN X
SCALE IN Y
SEQUENTIAL WRITE ITERATOR

FIG. 98



FIG. 99



FIG. 100



FIG. 102



FIG. 103

SUBSTITUTE SHEET



FIG. 104



FIG. 105


TILE OPACITY LOOKUP
FEEDBACK VSTRIP READ ITERATOR
IMAGE VSTRIP READ ITERATOR
BACKGROUND VSTRIP READ ITERATOR
432
SUB-PIXEL TRANSLATE
SCALE
PIXEL COMPOSITE
BACKGROUND VSTRIP WRITE ITERATOR
430
431
434

FIG. 106


TILE TEXTURE LOOKUP
SUB-PIXEL TRANSLATE
BACKGROUND TEXTURE VSTRIP WRITE ITERATOR
436
437

FIG. 107


TILE TEXTURE LOOKUP
SUB-PIXEL TRANSLATE
440
+ (255 LIMITED)
441
MAX
444
VSTRIP WRITE ITERATOR
445
N/4
442
BACKGROUND TEXTURE VSTRIP READ ITERATOR

FIG. 108

960720 "LOCKED"



FIG. 109


1/N TABLE LOOKUP
MULTIPLY
FEEDBACK VSTRIP WRITE ITERATOR
460
TILE TEXTILE LOOKUP
- (0 LIMITED)
SUB-PIXEL TRANSLATE
+ (255 LIMITED)
MAX
BACKGROUND VSTRIP WRITE ITERATOR
461
BACKGROUND TEXTURE VSTRIP READ ITERATOR
MIN
+ (255 LIMITED)
462
AVERAGE
SUB-PIXEL TRANSLATE

FIG. 110



FIG. 111



FIG. 112



FIG. 113



FIG. 114



FIG. 115



FIG. 116

SUBSTITUTE SHEET (RULE 26)



FIG. 117



FIG. 118



FIG. 119



FIG. 120



FIG. 121


LINE L+1
LINE L-1
LINE L
K1
C=1
CALCULATE
1/√X
YN
1/IINII
XN
LATCH 2
LATCH 1

FIG. 122



FIG. 123



FIG. 124

SUBSTITUTE SHEET (RULE 26)



FIG. 125



FIG. 126



FIG. 127



FIG. 128



FIG. 129



FIG. 130



FIG. 131



FIG. 132



FIG. 133



FIG. 134



FIG. 135



FIG. 136



FIG. 137



FIG. 138



FIG. 139



FIG. 140



FIG. 141



FIG. 142



FIG. 143



FIG. 144



FIG. 145



FIG. 146



FIG. 147


491
BUMP-MAP SEQUENTIAL READ ITERATOR1
492
BUMP-MAP SEQUENTIAL READ ITERATOR2
BUMP-MAP SEQUENTIAL READ ITERATOR3
490
K1
K2
CALCULATE N
XN
YN
1/||N||
CALCULATE N·L
CALCULATE DIFFUSE 2
K3
CALCULATE R·V
+
*
+
OUT-IMAGE SEQUENTIAL WRITE ITERATOR
K4
IMAGE SEQUENTIAL READ ITERATOR
CALCULATE SPECULAR 2.
+
OUT-IMAGE SEQUENTIAL READ ITERATOR
CALCULATE AMBIENT
2ND AND SUBSEQUENT LIGHTS

FIG. 148


CALCULATE L
1/||L||
CALCULATE f_{att}
K_3
Z_L
K_1
K_2
+
+
CALCULATE DIFFUSE 2
+
OUT-IMAGE SEQUENTIAL WRITE ITERATOR
IMAGE SEQUENTIAL READ ITERATOR
CALCULATE SPECULAR 2
+
OUT-IMAGE SEQUENTIAL READ ITERATOR
CALCULATE AMBIENT
2ND AND SUBSEQUENT LIGHTS

FIG. 149


BUMP-MAP SEQUENTIAL READ ITERATOR1
BUMP-MAP SEQUENTIAL READ ITERATOR2
BUMP-MAP SEQUENTIAL READ ITERATOR3
CALCULATE N
1/||N||
X_N
Y_N
+
K_1
+
K_2
CALCULATE N·L
CALCULATE L
X_L
Y_L
Z_L
CALCULATE R·V
CALCULATE f_{att}
CALCULATE DIFFUSE 2
*
K_3
+
*
+
OUT-IMAGE SEQUENTIAL WRITE ITERATOR
IMAGE SEQUENTIAL READ ITERATOR
CALCULATE SPECULAR 2
+
OUT-IMAGE SEQUENTIAL READ ITERATOR
CALCULATE AMBIENT
2ND AND SUBSEQUENT LIGHTS

FIG. 150


CALCULATE f_{att}
K_3
$1/|IL|$
X_L
Y_L
Z_L
CALCULATE L
CALCULATE f_{cp}
K_1
K_2
+
+
CALCULATE DIFFUSE 2
+
*
+
OUT-IMAGE SEQUENTIAL WRITE ITERATOR
IMAGE SEQUENTIAL READ ITERATOR
CALCULATE SPECULAR 2
+
OUT-IMAGE SEQUENTIAL READ ITERATOR
CALCULATE AMBIENT
2ND AND SUBSEQUENT LIGHTS

FIG. 151


BUMP-MAP SEQUENTIAL READ ITERATOR1
BUMP-MAP SEQUENTIAL READ ITERATOR2
BUMP-MAP SEQUENTIAL READ ITERATOR3
K3
CALCULATE N
CALCULATE fcp
+
K1
+
K2
YN
XN
1/IINII
XL
YL
ZL
CALCULATE N·L
CALCULATE L
CALCULATE R·V
CALCULATE fatt
CALCULATE DIFFUSE 2
+
+
OUT-IMAGE SEQUENTIAL WRITE ITERATOR
IMAGE SEQUENTIAL READ ITERATOR
CALCULATE SPECULAR 2
+
OUT-IMAGE SEQUENTIAL READ ITERATOR
CALCULATE AMBIENT
2ND AND SUBSEQUENT LIGHTS

FIG. 152







EACH SEGMENT CONTAINS 6 ROWS OF DOTS: ODD AND EVEN CYAN, MAGENTA, AND YELLOW.

FIG. 153



FIG. 154



FIG. 155


6 DOTS = 100μ M
6 DOTS = 100μ M
1 PIXEL = 6 X 6 DOTS
= 36 DOTS
= 100μ M SQUARE

FIG. 156



FIG. 157



FIG. 158



FIG. 159

9607420 T20ET63



FIG. 160

SUBSTITUTE SHEET



FIG. 161



FIG. 162



FIG. 163


42
626
13
623
660
661
662
641
640
621
620
637
639
633
635
631
632
53
630
624
636
677
647
646
645
622
654
655
656
612
627

FIG. 164



FIG. 165



FIG. 166



FIG. 167



FIG. 168



FIG. 169



FIG. 170



FIG. 171



FIG. 172



FIG. 173



FIG. 174



FIG. 175



FIG. 176



FIG. 177



FIG. 178



FIG. 179



FIG. 180


Filtered Clock
Clock Frequency Limiter
CLK
Programming Mode Detection Unit
OverUnder Power Detection Unit
Noise Generator
State Machine
Wait
OutBitValid
Cycle
CMD
InBitValid
I/O Unit
Serial I/O
InBitUsed
InBit
OutBit
ALU
Acc
Z
MTRZ
MinTicks Unit
Memory Unit
Address Generator
Adr
PC
C1Z
C2Z
Program Counter Unit
Control
1 bit
8 bits
9 bits (adr)
32 bits

FIG. 181


Start Address
0 0000 0000
Constants (16)
0 0001 0000
Reserved (48)
0 0100 0000
RAM (32)
0 0110 0000
Flash (32)
0 1000 0000
Program (384)
1 1111 1111
32-bit data entries
8-bit data entries

FIG. 182


Start Address
0 0000 0000
0x00000000
0x36363636
0x5C5C5C5C
0xFFFFFFFF
4 x 32-bit constants
0 0000 0100
0x5A827999 (y0)
0x6ED9EBA1 (y1)
0x8F1BBCDC (y2)
0xCA62C1D6 (y3)
4 x 32-bit y constants as used by SHA-1.
0 0000 1000
0x67452301 (h0)
0xEFCDAB89 (h1)
0x98BADCFE (h2)
0x10325476 (h3)
0xC3D2E1F0 (h4)
5 x 32-bit h constants as used by SHA-1.
Reserved (3)
Unused and unreferenced
0 0000 1111

FIG. 183


Start Address
0 0100 0000
E
D
C
B
A
A-E
0 0100 0101
T
Temp
0 0100 0110
H4
H3
H2
H1
H0
H0-4
0 0100 1011
B160 4
B160 3
B160 2
B160 1
B160 0
B160 0-4
0 0100 1111
Start Address
0 0101 0000
X15
X14
X13
X12
X11
X10
X9
X8
X7
X6
X5
X4
X3
X2
X1
X0
X0-15
0 0101 1111

FIG. 184


Start Address
0 0110 0000
R0
R1
R2
R3
R4
R0-4
0 0110 0100
Reserved
0 0110 0110
MT
0 0110 0111
AM
0 0110 1000
K1₄
K1₃
K1₂
K1₁
K1₀
K1₀-₄
Reserved
0 0110 1111
Start Address
0 0111 0000
M7
M6
M5
M4
M3
M2
M1
M0
M0-7
0 0111 1000
K2₄
K2₃
K2₂
K2₁
K2₀
K2₀-₄
Reserved
0 0111 1110
IST
0 0111 1111
ISW

FIG. 185


Start Address
0 1000 0000
Adr Table 1 (32)
0 1010 0000
Adr Table 2 (32)
0 1100 0000
DBR Table (8)
0 1100 1000
Program (312)
1 1111 1111

FIG. 186



FIG. 187



FIG. 188


Acc
VAL1
Acc (32bits+p)
OR
~Z
(1 bit)
VAL2
NOT
Z
WriteEnable
Logic1
MX1
ADD
AND
OR
XOR
RPL
ROR
inBitUsed
To OutBit
InBit
From MU
CMD
Cycle
MTRZ

FIG. 189


From Acc
Bit 0
To OutBit
XOR
MX1
RTMP
(1 bit)
MX2
ROR
1
ROR
2
ROR
27
ROR
31
MX3
From InBit
From MU
Bit 0
From MTRZ
Cycle
Logic1
InBitUsed
Logic2
CMD

FIG. 190


VAL1
MTR (32bits+p)
-1
Non-flashing
CMOS
Acc
0
MX1
Logic1
CMD
MTRZ
NOR
MTRZ
(1 bit)
VAL2
WriteEnable
Cycle

FIG. 191


SP (3 bits+p)
VAL1
-1
+1
MX1
Cycle
WriteEnable
PCA (6 x 9bits+p)
Select
VAL2
PC
0x01
ADD
MX3
Add Hi bit = 1
From MU
MX2
Add Lo bit = 0
Logic4
C1Z
C2Z
Z
Logic3
CMD
Logic2
Logic1

FIG. 192


From Address Generator
InBit
InBitValid
inBitUsed
8-bit Prog Flash
VAL1
8-bit data
Adr6-5
Adr3-0
Truth Table
Adr6
Logic1
Erase Part
VAL2
MX1
32-bit data
Adr4-0
32-bit Flash Memory
OR
Wait
CMD
Adr6-5
Logic2
WriteEnable
From ALU
VAL3
Adr4-0
32-bit RAM (p)
Adr6-4
WriteEnable
Logic3
WriteEnable
WE (1 bit)
Logic4
Cycle
CMD4

FIG. 193


PC
NOT
WriteEnable
Adr (9bits+p)
MX1
VAL1
Effective Address
Cycle
8-bit data
MX2
JSIGEN
DBRGEN
RPLGEN
K2MX
VARGEN
Cycle
Acc
JSRGEN
LDKGEN
CLRGEN
BITGEN
Cycle
C1
N
8-bit data
CMD
MX3
Counter Unit
C1Z
C2Z

FIG. 194



FIG. 195



FIG. 196



FIG. 197



FIG. 198



FIG. 199



FIG. 200



FIG. 201



FIG. 202


Cycle
Effective CMD
Truth Table
MX1
Logic2
Logic1
C2 (5 bits+p)
C1 (3 bits+p)
NOR
C1Z
bit3
-1
MX2
VAL1
C1
VAL2
NOR
C2Z
Logic3
MX3
0010
0111
1101
1111
N1 (4 bits+p)
N2 (4 bits+p)
N3 (4 bits+p)
N4 (4 bits+p)
Logic4
Logic5
Logic6
Logic7
MX4
-1
VAL3
N

FIG. 203

705

Data Type	Bits
Factory code	16
Batch number	32
Serial number	48
Manufacturing date	16
Media length	24
Media type	8
Preprinted media length	16
Cyan ink viscosity	8
Magenta ink viscosity	8
Yellow ink viscosity	8
Cyan drop volume	8
Magenta drop volume	8
Yellow drop volume	8
Cyan ink color	24
Magenta ink color	24
Yellow ink color	24
Remaining-media length indicator	16
Authentication key	128
Copyrightable bit pattern	512
Reserved for camera use	88
Total	**1024**

728

FIG. 204


774
775
776
INK COLOUR VISCOSITY
INK COLOUR DROP VOLUME
INK COLOUR
MEDIA TYPE
PULSE PROFILE CHARACTERIZER
771
REMAINING ROLL MEDIA
PRINT HEAD CONTROLLER
761

FIG. 205



FIG. 206



FIG. 207



FIG. 208



FIG. 209



FIG. 210



FIG. 211

SUBSTITUTE SHEET



FIG. 212



FIG. 213



FIG. 214



FIG. 215



FIG. 216



FIG. 217



FIG. 218



FIG. 219


42
POSTCARD ROLL
COUNTRY: AU
POSTAGE: $1.00
FORMAT: P
SUITABLE FOR: US. JP. UK.
EXPIRY: JAN. 2000

FIG. 220


902
ARTCAM APPLICATION
903
CAMERA MANAGER
906
IMAGE PROC. MANAGER
908
PRINTER MANAGER
910
UI MANAGER
905
FILE MANAGER
904
NETWORK MANAGER
907
CLOCK MANAGER
900
HARDWARE ABSTRACTION LAYER
DEVICE DRIVERS
CAMERA
IMAGE PROCESSOR
VLIW VECTOR PROCESSOR
PRINTER
MEMJET PRINTER
LCDS AND BUTTONS
STORAGE DEVICE
DOTCARD READER
PC CARD INTERFACE
NETWORK INTERFACE
IRDA INTERFACE
USB INTERFACE
REAL-TIME CLOCK
RISC PROCESSOR
REAL-TIME MICROKERNEL
911
901

FIG. 221


CAMERA MANAGER
903
CONTROL ZOOM
ZOOM MOTOR
CONTROL FOCUS
FOCUS MOTOR
LOCk FOCUS
913
AUTO FOCUS
918
SENSE SHARPNESS
IMAGE SENSOR
CHARGE FLASH
FLASH CHARGER
AUTO FLASH
919
SENSE LIGHTING
IMAGE SENSOR
CONTROL SPEED
AUTO EXPOSURE
920
SENSE LIGHTING
IMAGE SENSOR
CONTROL APERTURE
APERTURE MOTOR
SELF-TIMED CAPTURE
915
CONTROL SLF-TMR LED
SELF-TIMER LED
CAPTURE IMAGE
914
SENSE ORIENTATION
ORIENTATION SENSOR
SENSE MOTION
MOTION SENSOR
CONTROL RED-EYE LMP
RED-EYE LAMP
CONTROL SHUTTER
TRIGGER FLASH
FLASH TRIGGER
SENSE IMAGE
IMAGE SENSOR
VIEW SCENE
917
DISPLAY IMAGE
COLOR LCD
901

FIG. 222


IMAGE PROCESSING MANAGER
906
921
CONVERT AND ENHANCE IMAGE
923
DETECT FACES
VARK INTERPRETER
924
PARSE VARK SCRIPT
EXECUTE PARSE TREE
OPTIMIZE IMAGING GRAPH
EXECUTE IMAGING GRAPH
CONTROL IMAGE PROCESSOR
IMAGE PROCESSOR

FIG. 223


PRINTER MANAGER
908
PRINT IMAGE
930
HALF-TONE AND FORMAT IMAGE
CONTROL IMAGE PROC.
IMAGE PROCESSOR
UNCAP NOZZLES
CONTROL CAPPING SOLENOID
CAPPING SOLENOID
CLEAR NOZZLES
CONTROL PRINT HEAD
PRINT HEAD
ADVANCE PAPER TO PRINT HEAD
CONTROL PAPER T'PORT MOTOR
PAPER TRANSPORT MOTOR
PRINT AND ADVANCE
ADVANCE PAPER TO GUILLOTINE
CUT PAPER
CONTROL GUILLOTINE SOLENOID
GUILLOTINE SOLENOID
RETRACT PAPER TO PRINT ROLL
CAP NOZZLES
SENSE PAPER PULL
PAPER PULL SENSOR
UPDATE PRINT ROLL STATUS
CONTROL AUTH. CHIPS
ARTCAM AUTH. CHIP
931
AUTO MOUNT PRINT ROLL
AUTH. PRINT ROLL
PRINT ROLL AUTH. CHIP
SENSE PRINT ROLL
PRINT ROLL SENSOR

FIG. 224


USER INTERFACE MANAGER
910
PHYSICAL UI MANAGER
911
UPDATE STATUS DISPLAY
CONTROL STATUS LCD
STATUS LCD
UPDATE BUSY STATUS LED
CONTROL BUSY STATUS LED
BUSY STATUS LED
DISPATCH EVENT
SENSE SWITCH
CHP MODE SWITCH
SENSE BUTTON
LOCK FOCUS BUTTON
TAKE BUTTON
SELF-TIMER BUTTON
FLASH MODE BUTTON
PRINT BUTTON
HOLD BUTTON
DOTCARD EJECT BUTTON
GUI NAVIGATIO BUTTONS
DISPATCH VIRTUAL EVENT
912
GRAPHICAL UI MANAGER
UPDATE COLOR DISPLAY
CONTROL COLOR LCD
COLO R LCD

FIG. 225


FILE MANAGER
905
UNIFIED FILE SYSTEM MANAGER
VOLUME MANAGER
STORAGE DEVICE MANAGER
STORAGE DEVICE CONTROLLER
STORAGE DEVICE DRIVER
STORAGE DEVICE
DOTCARD DEVICE CONTROLLER
LOAD CARD
ILLUMINATE CARD
ADVANCE CARD
SENSE LINES AND ADVANCE
DECODE CARD
UPDATE STATUS LED
EJECT CARD
RETRACT CARD
CONTROL ILLUMINATION LED
CONTROL CARD T'PORT MOTOR
SENSE IMAGE LINE
CONTROL IMAGE PROCESSOR
CONTROL STATUS LED
SENSE CARD
ILLUMINATION LED
CARD TRANSPORT MOTOR
LINEAR IMAGE SENSOR
IMAGE PROCESSOR
STATUS LED
CARD SENSOR

FIG. 226

SEARCH REPORT



FIG. 227


1001
1010
1040
1009
1007
1020
1027
1008
1043
1011
1038
1035
1039
1036
1042
1033
1044
1023
1037

FIG. 228


1001
1010
1009
1008
1024
1043
1033
1025
1023
1026
1044
1027
1040
1007
1014
1016
1020
1015
1038
1041
1011
1039
1042

FIG. 229


1007
1035
1020
1035
1033
1029
1036
1034
1048
1031
1034
1032
1023
33
1044

FIG. 230

SUBSTITUTE SHEET (RULE 26)



FIG. 231